

Norfield



norfield.com

1-800-824-6242

1700 AUTOMATIC HINGE JAMB ROUTER


HIGH PRODUCTION HINGE JAMB ROUTER




Guards removed for photo



1 Quickly change hinge mortise locations without tools



2 Quick change turret stop system for various hinge backsets and sizes




3 Dust collection ready for cleaner and safer work environment



Throughput Rate

4-5
jamb/minute

| process | product | specs | features | options |
|--|--|---|--|--|
|  | <p>1700 Hinge Jamb Router</p> <p>Automatic hinge jamb routing up to 5 jams per minute</p> | <p>Hinge Specs 3" - 4-1/2"</p> <p>Jamb length 70" to 112"</p> <p>Jamb width 2-1/2" to 10-1/2"</p> <p>Jamb thickness 3/8" - 1-5/8"</p> <p>Electrical 115V @ 50 Amps</p> <p>Pneumatic 3 CFM @ 90 psi</p> <p>Floor Space req. (min.) 12' x 3'</p> <p>Approx. Shipping Wt 1100lbs</p> <p>Vacuum connection 4" duct</p> | <ul style="list-style-type: none"> • Quick change hinge locations • Accommodates a variety of jamb widths and lengths • Foot pedal operation for ease of use • Dust collection ready for operator safety • Mortise hinges from 3" to 4-1/2" | <ul style="list-style-type: none"> • 4 router module for 8'0" capability (3 router standard) • 1200 CFM vacuum |