

Norfield



norfield.com

3800 DOOR LITE MACHINE

1-800-824-6242


HEAVY DUTY DOOR LITE CUTTER WITH
OPTIONAL POWERED LATCH DRILL &
FACEPLATE MORTISOR

PROCESS RESIDENTIAL OR COMMERCIAL DOORS

COMPACT FOOTPRINT



Centralized panel allows the operator to control all machine functions from one position at the front of the machine.



Rotary lock bore template accommodates 1-1/2", 1-5/8", 1-3/4", and 2-1/8".



The 3800 comes with standard lock boring and optional powered latch boring and automatic faceplate mortising.





Optional overhead template speeds production.



Shown with optional overhead template



The popular 3800 is an efficient space saver for any door shop

process	product	specs	features	options
 	<p>3800 Door lite machine</p> <p>Process steel, fiberglass or wood doors.</p> <p>Cut any lite shape and prep for single or double lock. Compact machine footprint saves shop space.</p> <p>Standard oscillating quill prolongs bit life.</p>	<p>Door width up to 3'0"</p> <p>Door height up to 8'0"* <i>*May require repositioning</i></p> <p>Door thickness 1-3/8" to 1-3/4"</p> <p>Lock bore sizes 1-1/2", 1-5/8", 1-3/4", 2-1/8" Custom templates available</p> <p>Lock backset 2-3/8" & 2-3/4"</p> <p>Faceplate width up to 1-1/8"</p> <p>Faceplate length up to 2-1/2"</p> <p>Steel door skin thickness up to 18 gauge <i>(18 gauge requires 2 passes)</i></p> <p>Electrical 208V/230V 60Hz 3 Phase</p> <p>Pneumatic 3CFM @ 90 PSI</p> <p>Shipping wt up to 3000lbs</p>	<ul style="list-style-type: none"> Cuts any door lite shape Nine point clamping system secures door and template Adjustable spindle speed for cutting wood, fiberglass, or metal doors Dust collection ready 	<ul style="list-style-type: none"> Overhead template Automatic faceplate mortisor and powered latch drill Automatic pop-up roller system for easy door transfer Dust collection systems Optional waste bin Spare parts package Extended parts warranty