

Norfield



norfield.com


1-800-824-6242

4800XY DOOR LITE MACHINE

NO TEMPLATES REQUIRED FOR RECTANGULAR LITES

8-0 CAPABLE


FLOW-THROUGH DESIGN EXPEDITES PRODUCTION




Index bars include multiple stops for most rectangular lites, enabling quick, no-tool change-overs between common cutout shapes




Optional edge prep feature saves time by automatically drilling latch hole and mortising for faceplate during lite cutting



Cut lite shapes featuring a radius (such as oval or arch top) by using removable templates. Process multiple doors without handling template. No contact between template and door surface



X-Y axis locks reduce operator effort and ensure straight cuts that parallel stiles and rails



process	product	specs	features	options
	<p>4800XY Door lite machine</p> <p>X-Y style lite cutter capable of processing doors up to 8-0.</p> <p>Available accessory machines:</p> <ul style="list-style-type: none"> - 530/535 Door Loader - EDM Exterior Door Assembly System - 360S Outfeed Table 	<p>Door width 10" to 3'6" (Min. distance between edge of panel & lite cutout is 1.75")</p> <p>Door Height up to 8'0"</p> <p>Door thickness 1-3/8" to 2-1/4"</p> <p>Lock bore sizes 2-1/8" standard</p> <p>Lock backset 2-3/8" to 2-3/4"</p> <p>Faceplate Width up to 1-1/8"</p> <p>Faceplate Length up to 2-3/4"</p> <p>Electrical 208V/230V 3 Ph@15 Amps (no edge prep) 208V/230V 3 Ph@30 Amps (w/ edge prep) Pneumatic 5CFM @ 90 psi Shipping Wt. 3000lbs.</p>	<ul style="list-style-type: none"> • XY controls eliminate the need for templates when cutting rectangle door lites • Integrated template holder for non-rectangular lite shapes (i.e. oval, arch top, etc.) • Adjustable RPM speed control accommodates both wood/ fiberglass and metal cutting • Dust collection ready • Oscillating quill for greater bit life • Choice of 33-1/2" or 40" working height 	<ul style="list-style-type: none"> • Automated edge preparation • Waste bin • Vacuum for dust collection • Spare parts package • Additional index bars • 4'0" door width capacity • Extended warranty <p>Optional Waste bin</p>